

# Aquacon® ACI-P Series

Aviation Fuel Filter Cartridges

Remove Water and Dirt from Jet Fuel and Avgas

Inside-to-Out Flow Cartridges

EI1583 6th Edition Qualified



## FEATURES

- Free and emulsified water removal to less than 5 ppm
- ½ micrometer particulate removal
- Provide protection against “slugs” of water
- Pressure increase signals need for cartridge change
- Not affected by surface active agents\* (see caution info on back)
- Replace existing coalescers in into-plane filter/separator vessels
- Inside-to-out flow pattern
- Conductive End Caps



Aquacon® ACI Cartridges Construction

## Contact Information: DESCRIPTIONS

Parker Hannifin Corporation  
**Velcon Filtration Division**  
1210 Garden of the Gods Road  
Colorado Springs, CO 80907

phone 719 531 5855  
fax 719 531 5690  
vfsales@parker.com

www.velcon.com

Patented\* **Aquacon ACI-P** Filter Cartridges have a unique high-capacity inner filter media which removes all free and emulsified water from hydrocarbon fuels down to less than 5 ppm in the effluent. Absorbed water is chemically locked into this medium.

When the ACI-P reaches its water holding capacity, its accordion pleats swell, and cause an increase in the differential pressure which signals the operator to change the cartridge.

Solid contaminants are removed by the cartridge's two particulate filter media layers. The pleated media design allows

for large surface area and maximum dirt holding capacity. Performance is not affected by the presence of common surface active agents.

The **Aquacon** ACI-P open-end and threaded-base have been qualified to EI 1583, the “Energy Institute Specifications and Qualification Procedures for Aviation Fuel Filter Monitors with Absorbent Type Elements.”

The ACI-6xx01P (open-end) and ACI-6xx01PTB (threaded base) **Aquacon** elements can be installed in the final filter/separator vessel in place of coalescers for more protection against dirt and water downstream.



ENGINEERING YOUR SUCCESS.

## CARTRIDGE SELECTION TABLE

Model Number	O. D. Inches	Length Inches <sup>1</sup>	End-Cap Type	Max. Flow Rate (USGPM)	Interchange Information
ACI-61401P	6	14 ½	3 ½" ID Open-Ends	58	CC-N18, CA14-3, CA14-9
ACI-61401PTB	6	14	Screw Base/Blind	56	CC-N18SB, CA14-3SB, CA14-9SB
ACI-62201P	6	22 ¼	3 ½" ID Open-Ends	89	CC-K2, CC-K28, CA22-3, CA22-9
ACI-6220PTB	6	22	Screw Base/Blind	88	CC-K28SB, CA22-3SB, CA22-9SB
ACI-62901P	6	28 ¾	3 ½" ID Open-Ends	115	CC-N28, CA28-3, CA28-9
ACI-62901PTB	6	27 15/16	Screw Base/Blind	111	CC-N28SB, CA28-3SB, CA28-9SB
ACI-63301P	6	33 ¼	3 ½" ID Open-Ends	133	CC-K38, CA33-3, CA33-9
ACI-63301PTB	6	33	Screw Base/Blind	132	CC-K38SB, CA33-3SB, CA33-9SB Has NSN: 4330-01-439-2314
ACI-63301FP	6	33 3/8	2" ID Open-Ends	133	Faudi F. 1-842 (1.066.020)
ACI-63801P	6	38 ¼	3 ½" ID Open-Ends	153	CC-K38-1, CA38-3, CA38-9
ACI-63801PTB	6	38	Screw Base/Blind	152	CC-K38SB-1, CA38-3SB, CA38-9SB
ACI-64401P	6	43 ¼	3 ½" ID Open-Ends	173	CC-N38, CA43-3 CA43-9
ACI-64401PTB	6	44	Screw Base/Blind	176	CC-N38SB, CA43-3SB, CA43-9SB
ACI-65601P	6	57	3 ½" ID Open-Ends	228	CC-N48, CA56-3, CA56-9
ACI-65601PTB	6	56 1/6	Screw Base/Blind	224	CC-N48SB, CA56-3SB, CA56-9SB

<sup>1</sup> Overall length does not include the 1" bolt for the ACI-6xx01PTB threaded base ACI's.

Note: Drain vessels equipped with the Aquacon® ACI Cartridges on a daily basis from an upstream drain to ensure upstream water is removed to prolong element life.

### TECHNICAL INFORMATION\*

1. Maximum exposure temperature is 160°F.
2. Cartridges are rated at 1/2 micron nominal efficiency.
3. **Aquacon®** Cartridges can significantly reduce flow when loaded with water or dirt. Appropriate precautions should be taken in applications where fuel flow must be maintained or where surge conditions can occur.
4. Replace the cartridge if the differential pressure exceeds 25 psid. For service life information, please refer to Operating Procedure # 1839 or consult your company fuel handling procedures.
5. ACI burst strength exceeds 175 psid. If F/S vessel coalescer deckplate or manifold is not certified to 15 bar (220 psi) strength, a differential pressure limiting device, set from 25 - 30 psid, should be installed on the filter/separator vessel.
6. Typical water holding capacity for ACI-61401P: 900 ml.

© 2015 Parker Hannifin Corporation. Product names are trademarks or registered trademarks of their respective companies.  
Due to Velcon's continuing product improvement, drawings, specifications and pictures are subject to change without notice.

VEL1812R9 0615



Parker Hannifin Corporation  
**Velcon Filtration Division**  
 1210 Garden of the Gods Road  
 Colorado Springs, CO 80907 USA  
 tel +1 719 531 5855  
 www.velcon.com